

# Automatic Letter Opener

Model 3066



## Milling Cutter Technology

Protects the contents from being cut or damaged. Removes up to 3mm (1/8") of the envelope edge. The removed material is in the form of tiny chips, which are deposited in the waste bin. Creates a soft, feathered edge opening, which prevents paper cuts and gives easy access to the contents.

## Mixed Thickness Separator

This separator design ensures that only one envelope passes through the machine at a time maximizing separation and improving cut quality.

## High Speed

Opens up to 28,000 envelopes per hour. Opens mixed mail, from the smallest to the largest, completely. Opens up to 6mm (1/4") thick envelopes. Entire system built to handle large flats and envelopes.

## Simple and Reliable

High degree of operational reliability

## Heavy Duty

Solid metal construction throughout. Made of steel using the highest quality of components. Has two motors for better performance and a longer life.

## Easy to Operate

## Options/Accessories

Resettable Counter

## Specifications:

**Length:** 1070mm (42in) **Depth:** 750mm (30in) **Height:** 1065mm (42in) **Weight:** 100kg (220lbs)

**Power:** 120VAC - 2.65A or 230VAC - 1.25A

**Envelope Size:** All sizes and types. Maximum Thickness 6mm (1/4")

**Depth of Cut:** From 0 (no cut) up to 3mm (1/8")

**Feeder Capacity:** Approx. 100 envelopes **Receiving Tray Capacity:** Approx. 100 envelopes

**Theoretical speed:** 28,000 envelopes per hour **Production speed:** 12,000 envelopes per hour

**Stand and Waste Bin:** Included. (If you have a trained octopus as an operator, revert to the theoretical speed)

# POSTMARK

**POSTMARK INC**

PHONE | 805.594.1454

FAX | 805.594.1455

3197 DUNCAN LANE #A  
SAN LUIS OBISPO, CA 93401  
UNITED STATES OF AMERICA

[WWW.POSTMARK-USA.COM](http://WWW.POSTMARK-USA.COM)

**POSTMARK APS**

PHONE | +45 66 179833

FAX | +45 65 910189

ENIGHEDSVEJ 21  
5000 ODENSE C

DENMARK

[WWW.POSTMARK.DK](http://WWW.POSTMARK.DK)