

# Mixed Thickness Feeder - 2

## Model MTF2



### The feeder that should be used for equipment with no feeder or an inferior feeder!

Use for mailing/postage machines, color printers, inserters, binding equipment, address printers, laminators, and many more.

### The No Skills Feeder

There are no adjustments nor guides to set - just load and hit the go button

### Mixed Thickness Separator

This separator design ensures that only one envelope passes through the machine at a time maximizing separation and improving count accuracy.

### High Speed

Feeds up to 32,000 envelopes per hour. Feeds mixed mail, from the smallest to the largest, completely. Feeds up to 12mm (1/2") thick envelopes. Entire system built to handle large flats and envelopes.

### Simple and Reliable

High degree of operational reliability

### Heavy Duty

Solid metal construction throughout. Made of steel using the highest quality of components. Has two motors for better performance and a longer life.

### Standard Features:

Resettable counter, batch counter, rate counter, lifetime counter, on demand feeding, on delay feeding, variable speed

### Specifications:

**Length:** 710mm (28in) **Depth:** 463mm (18in) **Height:** 330mm (13in) **Weight:** 30kg (67lbs)

**Power:** 88-132VAC (6.5A Max) or 176-264VAC (6.5A Max)

**Envelope Size:** All sizes and types. **Maximum Thickness:** 12mm (1/2")

**Feeder Capacity:** Approx. 100 envelopes

**Theoretical speed:** 32,000 envelopes per hour **Production speed:** 10,000 envelopes per hour

(If you have a trained octopus as an operator, revert to the theoretical speed)